

Specification

Charts	42 Charts				
Distance of projection	2.5 - 8 m (8 m distance proje	ection screen is optional)			
Chart magnification	30x (When projected at 5 m distance)				
Lamp	LED Lamp				
Chart Rotation Speed	Average 0.3sec				
Power Save	11 minutes (after last signal)				
Tilt angle	± 20 degrees				
Resolution	50 lines / mm				
Program	2 programs with a maximum of 40 charts each				
Power Supply	100 - 240V~, 50/60Hz				
Power consumption	25 - 35VA				
Dimension	Body (Stand except)	200(W) × 290(D) × 172(H) mm			
	Body (Stand included)	200(W) × 290(D) × 235(H) mm			
	Remote Controller	64(W) × 196(D) × 20(H) mm			
Weight	Stand included	3.58 kg			
	Remote controller	160 g (Battery included)			
Standard Accessories	 Remote Controller Screen, Dust cover Power Cable Stand, T wrench Fuse, Battery 				
Optional Accessories	 Red / Green glasses Polarization glasses 				

*Designs and details can be changed without prior notice its impprovements.

Distributed by

Refined design and Compact size







40-4, Techno 2-ro, Yuseong-gu, Daejeon, 34015 Korea **Tel** +82.42.632.3536 **Fax** +82.42.632.3537 webmaster@potec.biz www.potec.biz


POTEC

www.potec.biz




PACP-8000 provides optometry with the greater convenience using the refined design, a compact size, and diversified charts.

PACP-8000 AUTO CHART PROJECTOR



C -	ARE ==	259 × 368 ×	m ∈ ш ∞ з п ∈ *	×
	L T H D V R NE F P K E O V A	92438 37956 48627		•••
0 0 0 0 0 = 0 0 0 0 0 0 = 0 0 0 0 0 0 =	RNEFP KNTDL HOPDV	73869 × 24395 * 52742 ×		
	RZNFD ALTOF KOFLA	56382 46298 83529		
0 0 0 0 C M 0 0 0 C C M 0 0 0 C C M M	TKALO ALTOF KOFLA		۲	
0 0 0 0 0 m 0 0 0 0 0 0 m 0 0 0 0 0 0 m	A O F T L # 0 R P O A # 2 E F V H #	(+)	•••	
•	•	"." "	:	2 * * * * 8 * * * *
-¦-	-}-	••••	1	
ROE		•		









Eyesight measurement using diversified charts

Diversified charts (4 types of A/C/D/R) per country are retained including binocular balance, aniseikonia, stereopsis, binocular vision test chart

Cost saving through adoption of LED light source

Maintenance & repair costs can be saved through adoption of LED light source having a semi-permanent service life



Bright & clear chart display

Brighter & clear chart display is provided by adoption of white LED